Listing of Claims

1.   (Currently Amended) A video communication system comprising a video encoder

and a video decoder, wherein the video encoder includes:

a data hiding processing unit for performing a data hiding operation based on an

error information received from the video decoder, and transmitting a processed error

information to the video decoder, the processed error information having a hidden data; and

a first error concealment processing unit for performing an error concealment

with reference to the error information, wherein the first error concealment processing unit

performs the error concealment for a frame that corresponds to the error information received

from the video decoder, the error concealment generating a reference frame on which the data

hiding operation is performed,

the data hiding operation including embedding a number of bits of the error

information into a frame currently being encoded, said embedding performed by modifying at

least one parameter of the frame currently being encoded depending upon whether remainders

of the parameter divided by 2 are equal to data to be hidden, and

wherein the video decoder includes:

a data extraction unit for extracting an information on an error frame, providing

the extracted frame information to the video encoder, and extracting the hidden data including

the embedded number of bits provided from the video encoder; and

a second error concealment processing unit for performing an error concealment

with reference to the extracted hidden data.

2.   (Canceled)

3.   (Previously Presented) The video communication system of claim 1, wherein the

processed error information is a frame number that corresponds to the reference frame, and

wherein the number of bits embedded by modifying said at least one parameter of the frame

currently being encoded is indicative of the frame number.

4.   (Previously Presented) The video communication system of claim 1, wherein the

extracted frame information is an information that represents whether or not the error occurs in

each group of blocks.

5.   (Previously Presented) The video communication system of claim 1, wherein said

at least one parameter is at least one of a quantization parameter corresponding to the frame

currently being encoded or a level value of a block to which a discrete cosine transform is

performed.

6.   (Previously Presented) The video communication system of claim 5, wherein the

level value corresponds to a value obtained by dividing a discrete cosine transform coefficient by

the quantization parameter.

7.   (Previously Presented) The video communication system of claim 1, wherein the

first and second error concealment processing units perform the error concealment by

calculating an average of motion vectors of blocks surrounding an error block and performing

motion compensation to a reference frame.

8.   (Original) The video communication system of claim 7, wherein the surrounding

blocks for obtaining the average of the motion vectors are upper and lower blocks of a block in

which the error occurs.

9.   (Currently Amended) A video decoder comprising:

        a variable length decoding processing unit for receiving a compressed video

stream from a video encoder and performing a variable length decoding;

        a data extraction unit for extracting a hidden data from the variable length

decoded stream, the hidden data being transmitted using a data hiding from the video encoder,

extracting an information on an error frame, and providing the extracted frame information to

the video encoder; and

an error concealment processing unit for performing an error concealment with reference to the extracted hidden data, wherein the hidden data is extracted based on a number of bits of error information embedded <u>in</u> a reference frame included in the compressed video stream, ~~said the number of bits embedded a value of at least one parameter of the reference frame~~,

<u>wherein the hidden data is hidden in the encoder by embedding the number of bits of error information into a frame currently being encoded, said embedding performed by modifying at least one parameter of the frame currently being encoded depending upon whether remainders of the parameter divided by two are equal to data to be hidden.</u>

10.   (Original) The video decoder of claim 9, wherein the hidden data is extracted during an inverse quantization.

11.   (Previously Presented) The video decoder of claim 9, wherein the at least one parameter includes at least one of a quantization parameter or a level value of a block to which a discrete cosine transform is performed.

12.   (Canceled)

13.   (Previously Presented) The video decoder of claim 9, wherein the extracted frame

information is an information that represents whether or not the error occurs in each group of

blocks.

14.   (Previously Presented) The video decoder of claim 9, wherein the error

concealment processing unit performs the error concealment by calculating an average of

motion vectors of blocks surrounding an error block and performing motion compensation to a

reference frame.

15.   (Currently Amended) A video coding method comprising:

        extracting an error frame information at a video decoder during a decoding and

providing the extracted error frame information from the video decoder to a video encoder;

        performing an error concealment at the video encoder based on the extracted

error frame information provided from the video decoder, the error concealment generating a

reference frame;

        performing a data hiding operation based on the reference frame, the data hiding

operation including embedding a number of bits of the extracted error frame information into a

frame currently being encoded, said embedding performed by modifying at least one parameter

of the frame currently being encoded <u>depending upon whether remainders of the parameter</u>

<u>divided by 2 are equal to data to be hidden</u>, and

transmitting the currently encoded frame containing the embedded number of bits

to the video decoder; and

extracting the embedded number of bits transmitted from the video encoder at the

video decoder, modifying a reference frame of a frame that is encoded, using the extracted

hidden data, and performing an error concealment at the decoder.

16.   (Previously Presented) The video coding method of claim 15, wherein the

extracted error frame information is an information that represents whether or not the error

occurs in each group of blocks.

17.   (Previously Presented) The video coding method of claim 15, wherein said at least

one parameter includes at least one of a quantization parameter or a level value of a block to

which a discrete cosine transform is performed.

18.   (Previously Presented) The video coding method of claim 15, wherein the video

encoder and the video decoder perform the error concealment by calculating an average of

motion vectors of blocks surrounding an error block and performing motion compensation to a

reference frame.

19.   (Previously Presented) The video communication system of claim 1, wherein the

data hiding operation is performed before quantization of the frame currently being encoded.

20.   (Previously Presented) The video coding method of claim 15, wherein the data

hiding operation is performed before quantization of the frame currently being encoded.